

# DHI-ASR2101A

## Access Reader



- PC material, acrylic panel and IP66, suitable for indoor and outdoor use.
- Support contactless recognition of IC card (Mifare card) .
- Support card/password unlock.
- Support communication through RS-485 and Wiegand 34 (Wiegand 26 can be configured).
- Support buzzer and indicator prompt.
- Support anti-tampering alarm.
- The built-in watchdog can detect and control abnormal operation status of the equipment and perform recovery processing to ensure the long-term operation of the equipment.
- All connection ports have overcurrent and overvoltage protection.

### Series Overview

As a key part of the access control system, the DHI-ASR2101A access control card reader supports card and password unlock, and sends the information to the access controller for verification. With a thin and elegant design, it is applicable to industrial zones, office buildings, schools, factories, stadiums, CBD, residential area, government properties, etc.

### Technical Specification

#### Basic

Product Type	Card reader
Buzzer	Yes
Casing	PC/acrylic panel

#### Function

Unlock Mode	Card swiping/password Multiple unlocking modes
Card Type	IC card
Modulation Type	AM
Frequency Range	13.56 MHz
Max Transmission Power	42 dBuA/m @10 m

#### Performance

Response Time	0.1 s
Card Reading Distance	0 cm–5 cm (0"–1.97")

#### Port

RS-485	1 channel
Wiegand	1 output channel

#### Alarm




Tamper Alarm	Yes
General	
Power Supply	12V 0.5A DC
Protection	IP66 (silicon sealant is needed, see the manual)
Power Consumption	Standby ≤ 0.9W, working ≤ 1.7W
Product Dimensions	123 mm × 86 mm × 15 mm (4.84" × 3.38" × 0.59") (L × W × H)
Packaging Dimensions	185 mm × 163 mm × 71 mm (7.28" × 6.41" × 2.80") (L × W × H, 1 in inner carton) 578 mm × 383 mm × 349 mm (22.76" × 15.08" × 13.74") (L × W × H, carton)
Operating Temperature	–30°C to +70°C (–22°F to +158°F)
Operating Humidity	5%RH–95% (non-condensing)
Operating Environment	Indoor; outdoor
Gross Weight	0.35 kg (0.77 lb)
Installation	Surface mount
Certifications	CE; FCC

### Ordering Information

Type	Model	Description
Access Reader	DHI-ASR2101A	DHI-ASR2101A Outdoor Waterproof Password IC Card Reader

Dimensions (mm[inch])



Application

