

IPMECD-0262-M50-LED

Barrier Rod



- 5 m straight arm that can be used on either side of the boom gate.
- Made of aluminum alloy, and designed with an anti-rust case that was treated with electrostatic spray.
- The pole has a light strip that can display red and green.
- Elastic anti-smashing rubber strip at the bottom.

Series Overview

Constructed from highly durable aluminum alloy, the Barrier Rod features an advanced anti-rust coating on its surface. Additionally, it is equipped with an elastic anti-collision rubber strip at the bottom for added protection.

Technical Specification

Basic	
Color	Red and white
Matched Product	DHI-IPMECD-2062 Series Barrier
General	
Operating Temperature	−40 °C to +70 °C (−40 °F to +158 °F)
Storage Temperature	−40 °C to +70 °C (−40 °F to +158 °F)
Operating Humidity	10%–90% (RH), non-condensing
Storage Humidity	10%–90% (RH), non-condensing
Casing Material	Metal (Aluminum)
Product Dimensions	5,000.0 mm × 115.0 mm × 45.0 mm (196.85" × 4.53" × 1.77") (L × W × H)
Packaging Dimensions	5,100.0 mm × 150.0 mm × 100.0 mm (200.79" × 5.91" × 3.94") (L × W × H)
Net Weight	7.0 kg (15.43 lb)
Gross Weight	7.4 kg (16.31 lb)
Installation	Compatible with barrier installation
Anti-corrosion Level	Basic Protection

Ordering Information

Type	Model	Description
Barrier Rod	IPMECD-0262-M50-LED	Barrier Rod

Dimensions (mm[inch])

