

DHI-IVD5148-11

48CH 1U INTELLIGENT VIDEO DEVICE





Launched by Dahua Technology, Dahua WizMind is a full portfolio of solutions composed of project-oriented products including IPC, IVSS,NVR, PTZ, XVR, Thermal and software platform which adopts industry-leading deep learning algorithms. Focusing on customer's requirements, WizMind provides precise, reliable and comprehensive Al solutions for verticals.

Series Overview

Dahua IVD is an AI edge computing device that combines traditional video management with intelligent video analytics. It provides real-time AI monitoring and high-speed data processing on-site. With its built-in deep learning module, this series offers high-precision AI functions including human face recognition, video metadata, and industrial algorithms, making it widely applicable to various industries and the perfect solution for upgrading traditional CCTV systems in the most cost-effective way.

Functions

Face Detection

Empowered by deep-learning algorithms, the device supports face detection, tracking, and capture, and outputs the best face snapshots. It supports analysis of up to 6 face attributes.

Face Recognition

Supports recording faces with incredible accuracy through metadata and real-time cross-check to recognize faces with target features. With Regular and Stranger face modes, the device triggers a wide variety of alarm actions to suit different situations.

- · 64-bit High-performance multi-core processor
- · Max 48-ch IP camera inputs
- · Max 256 Mbps incoming/recording/outgoing bandwidth
- · Up to 16-channel AI IVS
- · Up to 16-channel face recognition with normal IPC
- · Up to 32-channel face recognition with face detection IPC
- · Up to 16-channel video metadata
- · Up to 16-channel AcuPick with normal IPC
- · Up to 100 face databases with 500,000 face pictures in total
- · Up to 16-channel 1080p intelligent video compression
- · 1 SATA bay, Max.20 TB
- · 2 HDMI/1 VGA video output











Video Metadata

Metadata is the information on the features and attributes that is extracted from target objects which can be used for data retrieval. Currently, there are 4 main kinds of metadata in the security industry: Human face, human body, and motor vehicle and non-motor vehicle metadata.

IVS

Within specified restricted areas, intelligent detections are carried out, such as tripwire, intrusion, parking, people loitering and gathering. Driven by deep learning algorithms, IVS can provide precise person and vehicle classification detection, and accurately trigger alarms based on object types (pedestrians and vehicles), to greatly reduce the generation of false alarms. In addition, some basic functions including tripwire and intrusion are also referred to as perimeter protection.

AcuPick

This industry-leading search technology effectively utilizes both frontend and back-end intelligence to help with searching through massive video data to quickly and conveniently locate targets with greater precision.

Intelligent Video Compression

Dahua intelligent compression adopts the advanced self-adaptive bit rate control algorithm. It supports live view, playback and download by transmitting compressed streams through the network, to provide high-quality videos and reduce storage and network transmission costs.

Technical Specification			bottom type, bottom color, bag, rain coat, umbrella,	
System			hat, hairstyle, direction, hold a baby, face mask Vehicle: Vehicle type, vehicle color, plate color, logo,	
Main Processor	64-bit high-performance multi-core processor		calling, seatbelt, ornament Non-motorized Vehicle: Non-motor vehicle type, non	
Operating System	Embedded Linux OS		motor vehicle color, number of passengers, umbrella, rain coat, bag, sleeve, length, top color, hat, hair style,	
Operating Interface	Web (PCAPP); local GUI		face mask	
Al Card	1, AI card mode is switchable		 Supports match or mismatch attributes alarm for video metadata 	
Al Applications		IVS Analytics		
Al by Camera	Face detection; face recognition; video metadata (human; vehicle; non-motor vehicle); IVS; license plate comparison; tripwire people counting; regional people counting; abnormal number of people in queue; smoking detection; call detection; face & body detection	IVS	Al by Recorder: Supports 16-channel 2 MP or 16-channel 4 MP resolution Al by Camera: Supports 32-channel 2 MP or 32-channel 4 MP resolution Rules: Al by Recorder: climbing detection, tripwire, intrusion,	
AI by Recorder	Face detection; face recognition; video metadata (human; vehicle; non-motor vehicle); IVS		parking detection, crowd gathering, stay detection and loitering detection Al by Camera: tripwire, intrusion, abandoned object, missing object, fast moving, crowd gathering, loitering, parking and fence-crossing	
AcuPick	Al by Recorder: Supports 16-channel 2 MP or 16-channel 4 MP resolution. Al by Camera: Supports 32-channel 2 MP or 32-			
	channel 4 MP resolution	Video Diagnosis		
Face Detection	1. Al by Recorder: Supports 16-channel 2 MP or 16-channel 4 MP resolution 2. Al by Camera: Supports 32-channel 2 MP or 32-channel 4 MP resolution 3. Supports 6 properties: Gender, age, glasses,	Video Diagnosis	Supports 1-channel tour detection Supports 12 detection items: blurry video, low contrast, video tampering, video jitter, image freeze, overexposure detection, video loss, noise detection, scene changing, static noise, interference fringe and color cast	
	expression, face mask, and beard	Intelligent Video Compression		
Search by Image			1. Compressed preview, playback and download of	
Search by Image	Search by image in the face database, search by face or human body images, and 1:1 face recognition.		source stream on the platform. 2. Supports origin/compression dual stream live view and storage.	
Face Database Capacity	1.100 human face databases with 500,000 face pictures in total 2. 5 passerby databases with 500,000 face pictures in total The human face database and the passerby database share the total capacity and number of face images.	Intelligent Video Compression	 Supports compressing a variety of third-party code streams (ONVIF/RTSP). Compression Resolution: 12 MP/8 MP/6 MP/5 MP/4 MP/3 MP/1080p/1.3 MP/720p/D1. Each AI card supports up to 2-channel 12 MP/4-channel 8 MP/ 6-channel 5 MP/8-channel 4 MP/16-channel 2 MP and below. 	
		Industrial Algorithm	Industrial Algorithms	
	1. Al by Recorder: Supports 16-channel 2 MP or 16- channel 4 MP resolution with normal IP camera; 32-	Industrial Algorithms	The industrial algorithm is an optional installment.	
Face Recognition	channel with face detection IP camera (Totally 32 face pictures analyzed per second) 2. Al by Camera: supports 32-channel 2 MP or 32-channel 4 MP resolution 3. Supports entries frequency alarm	Work Behavior Analysis	1. Al by Recorder: Without large model (by default): 8-channel 2 MP/4 MP/8 MP (8-channel for each Al card) With large model(optional): 4-channel 2 MP/4 MP/8 M (4-channel for each Al card)	
Vehicle License Plate Comparison			Rules: Al by Recorder: calling, using mobile phone, sleeping while on duty, leave post detection, smoking	
License Plate Database Capacity	50 plate databases with 300,000 plate numbers in total Supports allowlist and blocklist		and abnormal number of people 1. Al by Recorder: 8-channel 2 MP/4 MP/8 MP (8-channel for each Alexad)	
Vehicle License Plate Comparison	Supports 32-channel 2 MP or 32-channel 4 MP resolution with ITC	PPE Detection	channel for each AI card) 2. Rules: AI by Recorder: hat/safety helmet detection, Balaclava, workwear detection (detect by color attributes or registered database), face mask detection,	
Video Metadata		5 5 6 5 6 5 11	goggles detection, seatbelt detection, safety vest	
Video Metadata	1. All by Recorder: Supports 16-channel 2 MP or 16-channel 4 MP resolution		detection, shoes detection, gloves detection, mask detection, exposed hair detection and arm band detection	
Video Metadata	2. Al by Camera: Supports 32-channel 2 MP or 32-			

	1 11 0 1 0 1 12 12 12 12 12 12 12 12 12 12 12 12 1		Storage	
Smart Object Detection	1. Al by Recorder: 8-channel 2 MP/4 MP/8 MP (8-channel for each Al card) 2. Rules: Al by Recorder: smart missing object and smart abandoned object 3. Object Type: non-motor vehicles, luggage, bags and		Record Management	Supports record control (continuous, event-based, scheduled, scheduled & event-based)
			Alarm	,
People Behavior Analysis	boxes 1. Al by Recorder: Without large model (by default): 8-channel 2 MP/4 MP/8 MP (8-channel for each Al card) With large model(optional): 2-channel 2 MP/4 MP/8 MP (2-channel for each Al card) 2. Rules: Al by Recorder: fighting detection, fall detection, running detection and tailing detection		General Alarm	Motion detection; tampering; IPC external alarm; heat alarm; temperature alarm; temperature difference alarm; hot spot alarm; cold spot alarm
			Anomaly Alarm	IPC offline alarm; storage error; HDD full; IP conflict; MAC conflict; login lock; AI module temperature alarm; AI module offline; fan malfunction; no HDD; network security exception; power exception
Audio and Video				Record; snapshot (full image); alarm uploading; remote
Access Channel	48-channel		Alarm Linkage	device alarm output; camera audio; buzzer; log; preset; email, and smart tracking. Disarming alarm linkage action by period or one-click sync disarm config with
Network Bandwidth Record	ncoming bandwidth: 256 Mbps Recording bandwidth: 256 Mbps Dutgoing bandwidth: 256 Mbps	Port	Port	channels
	32 MP;24 MP;16 MP;12 MP;8 MP;6 MP;5 MP;4 MP;3		Audio Input	1 channel
Resolution	MP;1080p;720p		Audio Output	1 channel
	1-channel 32 MP; 1-channel 24 MP; 2-channel 16 MP;		Alarm Input	4 channels
Decoding Capability	4-channel 8 MP@30 fps; 5-channel 6 MP@30 fps; 6- channel 5 MP@30 fps; 8-channel 4 MP@30 fps; 16-		Alarm Output	
	channel 1080p@30 fps; 36-channel 720p@30 fps		,	2 channels
Video Output	1-channel VGA output, 2-channel HDMI output, VGA 1/HDMI 1 outputs the same video source.		Disk Interface	1 slot, SATA3.0. Max.20 TB/HDD
Multi cara an Diantau	Max. 16-channel local live view		RS-232	1 port
Multi-screen Display	Max. 16-channel PCAPP live view		RS-485	1 port
Third-party Camera Access	ONVIF, RTSP, Sony, Panasonic, Axis, Arecont, Pelco, Canon, Samsung		USB	4 ports. 2 USB2.0 ports at the front panel and 2 USB3.0 ports at the rear panel.
Compression Standard			HDMI	2 ports. Port 1 supports 4K output.
Video Compression	Smart H.265+;H.265;Smart H.264+;H.264		VGA	1 port
Audio Compression	G.711a;G.711u;PCM;G.726		Network Port	2 RJ-45 10/100/1000Mbps self-adaptive Ethernet ports
Network			Power	Single supply
	HTTP;HTTPS;TCP/ IP;IPv4;RTSP;UDP;SMTP;NTP;DHCP;DNS;DDNS;P2P;IPv6; UPnP;SNMP		General	
Network Protocol			Disk Bay	1
Mobile Phone Access	DMSS		Form Factor	1U
Interoperability	ONVIF (Profile S, T and G); CGI; SDK		Power Supply	12 VDC,5 A
Browser	Chrome; PCAPP; IE9 or higher; Firefox		Power Consumption	18 W (without HDD, idling) 25 W(all HDDs connected)
Network Mode	Multiple-address mode;Load balance;Fault-tolerance;Link aggregation		Fan	Intelligent speed regulation fan
Recording Playback	tolerance, and appreparion		Net Weight	1.75 kg (3.86 lb)
Multi-channel Playback	Max. 16-channel playback		Gross Weight	2.78 kg (6.13 lb)
Record Mode	Search auto; manual; video detection; IO alarm;		Product Dimensions	Chassis: 304 mm × 223.8 mm × 43.5 mm (11.97" × 8.11" × 1.71") (W × D × H)
Storage Method	thermal imaging; intelligent event; all record file Internal HDD		Packaging Dimensions	With packaging: 399 mm × 304 mm × 133 mm (15.71" × 11.97" × 23.58") (W × D × H)
Backup Method	HDD, peripheral USB storage device		Operating Temperature	-10 °C to +55 °C (+14 °F to +131 °F)
Playback Function	Play; Pause; Stop; Fast forward; Fast backward; Reverse play; Frame by frame; Full-screen; Backup (clip and file); Snapshot; Digital zoom; Audio on and off		Operating Humidity	10%–90% (RH), non-condensing
			Operating Altitude	≤5,000 m (16,404.20 ft)
			Installation	Desktop; Rack



CE-LVD: EN 62368-1
Certifications
CE-EMC: EN IEC 6100


CE-EMC: EN IEC 61000-3-2, EN 61000-3-3, EN

55032 , EN 50130-4 , EN 55035

Ordering Information						
Туре	Model	Description				
INTELLIGENT VIDEO DEVICE	DHI-IVD5148-1I	48CH 1U INTELLIGENT VIDEO DEVICE				


Dimensions (mm[inch])

mm [inch]





Panels



1 Alarm In/Out

2 AUDIO IN

3 AUDIO OUT

4 USB Port

5 Network Port

6 HDMI Port

7 RS-232 Port

8 VGA Port

9 Power Input

10 Ground