

# Akin 2000


PN: PWAV-20002AK-AZ01B

EAN: 6422956005443

*The worthy protector*



Digital display



Time delay function



Selectable input voltage range



## ★ Features

- ⊕ Microprocessor control guarantees high reliability
- ⊕ Selectable input voltage range
- ⊕ Time delay function eliminates transients that can effect connected equipment
- ⊕ Under-voltage, over-voltage, over-heat and over current protection
- ⊕ Provides stable output voltage
- ⊕ Provide surge and spike suppression




## 📄 Specifications

|                    |   |
|--------------------|---|
| <b>Capacity</b>    | 2000VA / 1600W                                      |
| <b>Socket type</b> | 2x schuko   |
| <b>Input</b>       |   |
| Nominal Voltage    | 220 VAC   |
| Voltage Range      | 110 VAC - 270 VAC or 140 VAC - 260 VAC (Selectable) |
| Frequency Range    | 60 Hz or 50 Hz                                      |
| <b>Output</b>      |   |
| Nominal Voltage    | 220 VAC   |
| Voltage Regulation | ± 10%   |
| <b>Efficiency</b>  |   |
| Normal Mode        | 95%   |
| AVR Mode           | 92%   |
| <b>Protection</b>  |   |
| Delay Time         | 3 minutes or 10 Seconds                             |

|   |  |
|---|--|
| <b>Full Protection</b>                      | over-voltage<br>under-voltage<br>over-heat<br>over current protection      |
| <b>Indicators</b>                           |  |
| <b>LED Indicator</b>                        | normal indicator<br>AVR indicator<br>delay time setting<br>fault indicator |
| <b>Normal Mode</b>                          | Green lightning  |
| <b>Activate voltage range switch Mode</b>   | Yellow & Green led lighting  |
| <b>Output Adjustable Voltage Range Mode</b> | Red & Green led lighting   |
| <b>Time Delay</b>                           | Red led Flashing & Green lighting  |
| <b>Digital Display</b>                      | Input and output voltage   |

|                           |  |
|---------------------------|--|
| <b>Physical</b>           |  |
| Dimension, D X W X H (mm) | 233.6 x 134 x 181                            |
| Net Weight (kgs)          | 6.55   |
| <b>Environment</b>        |  |
| Operating Temperature     | 0- 40°C                                      |
| Humidity                  | 0-90 % relative humidity<br>(Non-condensing) |

## Logistics

|  |                                |
|--|--------------------------------|
|  Carton Box Size          | 260 x 323 x 596 mm             |
|  Pieces in the Carton Box | 3 pcs / ctn                    |
|  Net & Gross weight / CTN | N.W. / G.W.: 21.1 kg / 21.9 kg |

## Certificates

